

Fixture Type:	
Model Number:	
Project:	

## C Series Steel Emergency Lighting



### ORDERING GUIDE

<b>CL</b>	<b>- 2</b>	<b>- V</b>
↓	↓	↓
<b>CAPACITY</b> CL 6V, 18W CH 6V, 24W CR 6V, 36W	<b>Housing Color</b> 2 White 3 Black 4 Grey	<b>OPTIONS</b> See below




### OPTIONS

V	Voltmeter*
A	Ammeter*
0H	No Heads
1H	1Head
TD	Time Delay
SM	Side Mounted Heads
ML	Metal Heads
CP	Cord and Plug (120 VAC)
NI	Nickel Cadmium Battery
RT	Remote Test

\* Only one meter may be installed.

### RT - Remote test (Optional)

Allows user to initiate a momentary test of the emergency lighting from up to 20 feet away. Infra red remote (IRT) not included. required, not included.



### DIMENSIONS

Models	Length (in)	Height (in)*	Width (in)
All	9¾	12½	2¾

\* Measured to the top of the lighting heads.

### STANDARD FEATURES

- Universal 120/277 volt 60 Hz input - other volt-ages available upon request
- Fully automatic solid state charger returns bat-tery to full charge according to UL guidelines
- Solid state relay supervision
- Low battery voltage disconnect
- AC lockout
- Brownout protection.
- High charge and AC ready LED indicators.
- Test switch
- Long life maintenance free valve regulated lead acid battery
- Minimum of 90 minutes of emergency illumina-tion.
- Heavy duty steel construction with a bright white finish. (Other colors available)
- Supplied with two top mounted PAR36 type heads with 7.2 watt wedge base lamps.
- Remote test is available and requires an Infra Red hand held tester.
- **MADE IN THE USA**

### AGENCY APPROVALS

ETL Listed to UL924.  
Meets or exceeds the requirements of the National Electrical Code and NFPA 101.

### WARRANTY

One year warranty from date of shipment on entire unit. Battery will carry additional pro-rata warranty. See Warranty Statement for details.