

Fixture Type:	
Model Number:	
Project:	

## D Series Steel Emergency Lighting



### ORDERING GUIDE

<b>D</b>	<b>- 2 -</b>	<b>6</b>	<b>-60</b>	<b>- E</b>
↓	↓	↓	↓	↓
<b>Housing Color</b> 2 White 3 Black	<b>VOLTAGE</b> 6 6 Volts 12 12 Volts	<b>CAPACITY</b> 56 56 Watts <sup>2</sup> 60 60 Watts 90 90Watts 100 100 Watts <sup>1</sup>	<b>OPTIONS</b> See below	

### OPTIONS

- V Voltmeter\*
- A Ammeter\*
- RT Remote Test
- E Self Diagnostics\*\*
- TD Time Delay
- 0H No Heads
- 1H 1Head
- 3H 3 Heads
- SM Side Mounted Heads
- ML Metal Heads
- CP Cord and Plug (120 VAC)
- NI Nickel Cadmium Battery - 12 volt 56 watt unit only


\* Only one meter may be installed.  
 \*\* Not available with NiCad units  
<sup>1</sup> 12 Volt units only  
<sup>2</sup> 12 volts Nickel Cadmium batteries only

### SELF-TEST / DIAGNOSTIC (Optional)

- Microprocessor controlled state of the art self-diagnostic system
- Automatic 15 minute monthly and 90 minute yearly discharge tests
- Visual and Audible indicators for the following conditions:
  - Transfer failure
  - Charger malfunction
  - Defective battery
  - Burnt out lamp

### RT - Remote test (Optional)

Allows user to initiate a momentary test of the emergency lighting from up to 20 feet away. Infra red remote (IRT) not included.



### DIMENSIONS

Models	Length (in)	Height (in)*	Width (in)
All	12 $\frac{1}{2}$	14 $\frac{1}{8}$	4 $\frac{3}{4}$

\* Measured to the top of the lighting heads.

### STANDARD FEATURES

- Universal 120/277 volt 60 Hz input - other voltages available upon request
- Fully automatic solid state charger returns battery to full charge according to UL guidelines
- Solid state relay supervision
- Low battery voltage disconnect
- AC lockout
- Brownout protection.
- High charge and AC ready LED indicators.
- Test switch
- Long life maintenance free valve regulated lead acid battery
- Minimum of 90 minutes of emergency illumination.
- Heavy duty steel construction with a bright white finish. (Other colors available)
- Supplied with two top mounted PAR36 type heads with 7.2 watt wedge base lamps.
- Remote test is available and requires an Infra Red hand held tester.
- **MADE IN THE USA**

### AGENCY APPROVALS

ETL Listed to UL924.  
 Meets or exceeds the requirements of the National Electrical Code and NFPA 101.

### WARRANTY

One year warranty from date of shipment on entire unit. Battery will carry additional pro-rata warranty. See Warranty Statement for details.