

Fixture Type:	
Model Number:	
Project:	

PBU Series High Capacity Commercial Emergency Lighting



ORDERING GUIDE

PBU	-650	-HTR
↓	↓	↓
MODEL PBU	CAPACITY 650 6 Volts 50 Watts 6100 6 Volts 100 Watts 1250 12 Volts 50 Watts 12100 12 Volts 100 Watts	OPTIONS HTR Heater

ILLUMINATION

- Fully adjustable PAR36 type lamp heads
- Metallized reflector and plastic lens offers optimal light distribution.
- 6 volt units are provided with 7.2 watt HIT lamps
- 12 volt 50 watt units are provided with 9 watt HIT lamps
- 12 volt 100 watt units are provided with 12 watt HIT lamps
- Optional lamps are available, contact factory

HOUSING

- Injection-molded, engineering-grade, 5VA flame retardant, high impact thermoplastic construction in light grey finish.
- Knockouts on the back for wall mounting
- Side and top knockouts for conduit entry

DIMENSIONS

Models	Length (in)	Height (in)*	Width (in)
50 watt units	12¾	14¾	3¾
100 watt units	12¾	14	5

STANDARD FEATURES

- Universal 120/277 volt 60 Hz input
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.
- Internal solid-state transfer switch automatically connects the internal battery to lamp heads
- Low battery voltage disconnect
- AC lockout
- Brownout protection
- Charge / Ready LED indicator
- Test switch
- 6 volts sealed lead calcium battery
- Minimum 90 minutes of emergency illumination.

AGENCY APPROVALS

Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
UL listed for damp locations. (20°C – 50°C)

WARRANTY

Five year warranty on all electronics and housing.
Battery is pro-rated for two years.